

APPROVAL OF MANUFACTURER CERTIFICATE

Certificate no.:
AMMM00000KM
Revision No:
4

This is to certify:

that

EUSKAL FORGING S.A. SESTAO PLANT
Calle Altos Hornos de Vizcaya 25, 48910 Sestao, Bizkaia,
Spain

is an approved manufacturer of
Steel Forgings

in accordance with

DNV rules for classification – Ships
DNV rules for classification – Naval vessels
DNV-OS-B101 – Metallic materials
DNV class programme – DNV-CP-0247 Steel forgings

and the following particulars:

Application area	Forgings for hull structures and equipment Forgings for shafting and machinery Forgings for gearing Forgings for boilers, pressure vessels and piping systems Ferritic steel forgings for low temperature service Liquid quenched and tempered structural steels
Steel type	Carbon and carbon-manganese Alloy
Forging method	See page 2 ff.
Max. weight	See page 2 ff.
Max. thickness	See page 2 ff.
Heat treatment condition	See page 2 ff.

Manufacturer(s) approved by this certificate is/are accepted to deliver according to DNV GL, DNV and GL rules.
Materials to be applied to DNV classed object shall fulfill the material requirements in the applicable DNV class rules.

Issued at **Hamburg** on **2026-05-21**

This Certificate is valid until **2029-06-18**.

DNV local unit: **Area NB/CMC Iberia**

Approval Engineer: **Stefan Röhr**



for **DNV**

This document has been digitally signed and will
therefore not have handwritten signature

Christian Wildhagen

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.

Particulars of the approval

Forgings for hull structures and equipment

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. thickness [mm]	Heat treatment condition ²⁾
C and C-Mn	NV F400UW, NV F440UW, NV F480UW, NV F520UW, NV F560UW, NV F600UW	RR/OD	30 000	504	QT
C and C-Mn	NV F480UW	RR/OD	85 000	504	N
Alloy	NV F550AW, NV F600AW, NV F650AW	RR/OD	30 000	504	QT

Forgings for shafting and machinery Forgings for gearing

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. thickness [mm]	Heat treatment condition ²⁾
C and C-Mn	NV F400U, NV F440U, NV F480U, NV F520U, NV F560U, NV F600U, NV F640U, NV F680U, NV F720U, NV F760U	RR/OD	30 000	504	N
C and C-Mn	NV F480U	RR/OD	85 000	504	N
Alloy	NV F600A, NV F700A, NV F800A, NV F900A, NV F1000A, NV F1100A	RR/OD	30 000	504	QT

Forgings for boilers, pressure vessels and piping systems

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. thickness [mm]	Heat treatment condition ²⁾
C and C-Mn	F450H, F490H	RR/OD	85 000	504	N
Alloy	F0.5Mo F1Cr0.5Mo F2.25Cr1Mo	RR/OD	30 000	504	QT

Ferritic steel forgings for low temperature service

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. wall thickness [mm]	Heat treatment condition ²⁾
C and C-Mn	F450L, F490L	RR/OD	30 000	504	N

Liquid quenched and tempered structural steels

Steel type / grade	Forging method ¹⁾	Max. weight [kg]	Max. thickness [mm]	Heat treatment condition ²⁾
NV-M550	RR	30 000	800	QT
HY-80 acc. to MIL-S-23009C	RR	30 000	800	QT
15NiCrMo10-6 ³⁾	RR	30 000	800	QT

Remarks:

- 1) RR: Ring Rolling; OD: Open die forging
- 2) N: Normalised; QT: Quenched and Tempered
- 3) Chemical analysis as per WL 1.6780-3. Properties acc. to Zeile 9 to 20 as per WL 1.6780-3. Other parts of WL 1.6780-3 are not covered by this approval.