

APPROVAL OF MANUFACTURER CERTIFICATE

This is to certify:

That
EUSKAL FORGING, S.A
IRURA PLANT
Irura, GUIPUZCOA, Spain

is an approved manufacturer of
Steel Forgings

in accordance with
DNV GL rules for classification – Ships
DNVGL-OS-B101 – Metallic materials

and the following particulars:

Application area	Forgings for hull structures and equipment, Forgings for shafting and machinery, Forgings for gearing, Forgings for boilers, pressure vessels and piping systems, Ferritic steel forgings for low temperature service, Stainless steel forgings
Steel type	Carbon and carbon-manganese, Alloy, Austenitic stainless, Martensitic stainless, Ferritic-austenitic (duplex) stainless
Forging method	Open die forging/Ring Rolling
Max. weight	See page 2 ff.
Heat treatment condition	See page 2 ff.

Manufacturer(s) approved by this certificate is/are accepted to deliver according to DNV GL, DNV and GL rules. Materials to be applied to DNV GL classed object shall fulfill the material requirements in the applicable DNV GL class rules.

Issued at **Hamburg** on **2020-01-21**

for **DNV GL**

This Certificate is valid until **2022-12-31**.

DNV GL local station: **Bilbao**

Approval Engineer: **Stefan Röhr**

.....
Thorsten Lohmann
Head of Section



Job Id: **263.11-007058-2**
 Certificate No: **AMMM00000KN**
 Revision No: **2**

Particulars of the approval

Forgings for hull structures and equipment

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. section [mm]	Heat treatment condition ²⁾
C and C-Mn	VL F400UW, VL F440UW, VL F480UW, VL F520UW, VL F560UW, VL F600UW	OD/RR	10 000	500	N, NT, QT
Alloy	VL F550AW, VL F600AW, VL F650AW	OD/RR	10 000	500	QT

Forgings for shafting and machinery

Forgings for gearing

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. section [mm]	Heat treatment condition ²⁾
C and C-Mn	VL F400U, VL F440U, VL F480U, VL F520U, VL F560U, VL F600U, VL F640U, VL F680U, VL F720U, VL F760U	OD/RR	10 000	500	N, NT, QT
Alloy	VL F600A, VL F700A, VL F800A, VL F900A, VL F1000A, VL F1100A	OD/RR	10 000	500	QT

Forgings for boilers, pressure vessels and piping systems

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. section [mm]	Heat treatment condition ²⁾
C and C-Mn	VL F450H, VL F490H	OD/RR	10 000	500	N, NT, QT
Alloy	VL F0.5Mo, VL F1Cr0.5Mo	OD/RR	10 000	500	N, NT, QT
	VL F2.25Cr1Mo	OD/RR	10 000	500	N, QT

Ferritic steel forgings for low temperature service

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. section [mm]	Heat treatment condition ²⁾
C and C-Mn	VL F450L, VL F490L	OD/RR	10 000	500	N, NT, QT
Alloy	VL F3.5Ni, VL F5Ni, VL F9Ni	OD/RR	10 000	500	NT, QT

Job Id: **263.11-007058-2**
Certificate No: **AMMM00000KN**
Revision No: **2**

Stainless steel forgings

Steel type / grade ⁴⁾	Forging method ¹⁾	Max. weight [kg]	Max. section [mm]	Heat treatment condition ²⁾
Austenitic Stainless	OD/RR	10 000	500	SHT
Ferritic-austenitic Stainless (22 Cr Duplex)	OD/RR	10 000	500	SHT
Martensitic Stainless	OD/RR	10 000	500	QT

Remarks:

- ¹⁾ OD: Open Die Forging; RR: Ring Rolling
- ²⁾ QT: Quenched and tempered; N: Normalised; NT: Normalised and tempered
SHT: Solution Heat Treated (Solution Annealing)
- ³⁾ Incl. equivalent grades in acc. to other standards
- ⁴⁾ Stainless steel forgings shall be in accordance with recognized standards, e.g. EN 10222, EN 10250, EN 10088, ASTM A473/A965/A1049 and JIS G 3214, provided that supplementary requirements contained herein are also met. Recognition of other standards is subject to submission to the Society for evaluation.